




DuPont Automotive Finishes

## DuPont™ Sontara® PS-3909S™ Low VOC Wipes

### Description


A versatile pre-saturated wipe containing an ultra-low VOC (0.5 lbs/gal) multi-purpose cleaner. The DuPont™ Sontara® PS-3909S™ Low VOC Pre-Saturated Wipe is designed to remove sanding sludge, grease smears, dirt and compound sludge prior to painting. The wipes are used with an easy dispensing canister that keeps wipes saturated for effective cleaning.

### General Information




#### Components

DuPont™ Sontara® PS-3909S™ Low VOC Kit (dispensing canister with wipes)  
 DuPont™ Sontara® PS-3909S™ Low VOC Pack (wipes refill in foil pouch)



#### Mix Ratio

Ready to use.



#### Application

##### Substrates

DuPont topcoats  
 Sanded substrates  
 OEM finishes  
 Cured, repainted surfaces  
 Sanded primers  
 Cured sealers




#### Application

Apply moderate pressure and smooth even strokes from end to end when wiping the surface with the DuPont™ Sontara® PS-3909S™ Low VOC Wipe. Use a clean section of the wipe with each stroke to avoid contaminant deposition.

Wipe the surface while it is still wet to loosen and lift the contaminants; follow immediately by wiping dry thoroughly with a clean DuPont™ Sontara® Solvent Wash and Dry Cloth (E-4143 or E-4142).

For hard to remove surface contamination, repeat previous step.

If streaks appear or surface appears non-uniform, repeat cleaning procedure.



#### Storage

Store at room temperature. Do not store in areas subject to freezing temperatures.

## DuPont™ Sontara® PS-3909S™ Low VOC Wipes

### Physical Properties

---

VOC: 0.5 lbs./gal. as packaged (8.1 lbs./gal. LE)  
Flash Point: 200°F

### VOC Regulated Areas

---

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing and usage recommendations in the VOC Compliant Products Chart for your area.

### Safety and Handling

---

Before using any DuPont Refinish product, be sure to read all safety directions and warnings. WEAR A PROPERLY FITTED AIR PURIFYING RESPIRATOR with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A), eye protection, gloves and protective clothing during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air purifying respirator fit is not possible, wear a positive-pressure, supplied air respirator (NIOSH TC-19). In all cases follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. This product is intended for industrial use only by professional, trained painters.